



WWW.SMITTYBILT.COM

## **Installation Instructions**

Part # 5665201  
Molle Roll Bar Padding Kit

03-06 Jeep Wrangler (TJ)

Please read instructions entirely before installing this product. It is recommended to install this product when temperatures are above 70 degrees.

**Step 1:** If equipped with, remove the hardtop or soft top. Using a T30 Torx bit disconnect soft top bow assembly from brackets on sport bar. Leave the brackets bolted on, remove the door surrounds as well.

Using the T30 Torx bit remove the over head speaker pods. Once pods are loosened you will see the wire connector, disconnect and set speaker pod and hardware to the side. They will be re-installed later.

**Step 2:** Using a T50 Torx bit, Remove front and rear seat belt bolts where they attach to the sport bar. (Save for re-install later) Now remove existing sport bar cover, you may need to cut certain sections off. Note: Do not remove the OE foam core on sport bar.

**Step 3:** Loosely lay the main piece over the sport bar. (Fig A)

**Step 4:** Line the pre-cut holes on the back side of the center cover with the holes on the sport bar that the speaker pod pin and wire were installed. (Fig B, C) Then Zip the center section up.



(Fig A)



(Fig B)

**For Technical Support/Warranty Information please call 310-762-9944**

**Smittybilt, 400 West Artesia Blvd, Compton, CA 90220**



WWW.SMITTYBILT.COM

## Installation Instructions

Part # 5665201  
Molle Roll Bar Padding Kit

03-06 Jeep Wrangler (TJ)

**Step 5:** Wrap the fabric around the side uprights, sliding the flanges on the soft top bow assembly bracket through the slots on the pad kit. (Fig D) Line up the pre-cut holes with the seat belt attaching points. (Fig E)



(Fig C)



( Fig D)



(Fig E)

**Step 6:** Pulling the cover together, slowly zip up the sides. (Fig F)

**Step 7:** Pulling the cover together, slowly zip up the rear bottom sections, lining the pre-cut hole up with the seat belt attaching point. (Fig G, H) Then proceed to zip the upper to zip the top portion of the rear bars towards the front making sure the pre-cut holes for the speaker pod line up with the holes on the sport bar.



(Fig F)



(Fig G)



(Fig H)

**For Technical Support/Warranty Information please call 310-762-9944**

**Smittybilt, 400 West Artesia Blvd, Compton, CA 90220**



WWW.SMITTYBILT.COM

## ***Installation Instructions***

Part # 5665201  
Molle Roll Bar Padding Kit

03-06 Jeep Wrangler (TJ)

**Step 8:** The zippers for the rear, center and side bars should come close together above the front seat belts. (Fig I) Pull the flap around and snap onto pad kit. (Fig J)



(Fig I)



(Fig J)

**Step 9:** Make any necessary adjustments on cover and then re-install previously removed seat belt bolts and speaker pods. Note: Loctite is recommended to use when re-installing seat belt bolts.

**Step 10:** Install the front horizontal bar covers. Make sure the openings on the cover align with the mounting locations for the door surrounds. (Fig K) Note: the zipper goes on the inside of the vehicle.



(Fig K)

**For Technical Support/Warranty Information please call 310-762-9944**

**Smittybilt, 400 West Artesia Blvd, Compton, CA 90220**



WWW.SMITTYBILT.COM

## Installation Instructions

Part # 5665201  
Molle Roll Bar Padding Kit

03-06 Jeep Wrangler (TJ)

Step 11: Make any necessary adjustments then re-install door surrounds and top. Installation is now complete. (Fig L,M)



(Fig L)



(Fig M)

### Notes

- Make sure all hardware is completely secured when done
- When installing its best to squeeze the cover together and zip up slowly
- Do not force the zippers, this may cause damage to padding kit.
- If any OE foam is still exposed you can carefully trim it off with a sharp blade
- Molle bags can be attached anywhere Molle webbing is located on cover.
- If OE foam core pieces are broken tape them around sport bar to prevent movement while installing padding kit.

### Limited Warranties

Smittybilt's products are covered under the following limited warranties only. Note that the duration of the limited warranty differs according to the material and finish of the product purchased. Subject to the duration and conditions of the limited warranty stated below, Smittybilt warrants to the original retail purchaser that its products are free from defects in material and workmanship. All other warranties and representations express or implied, are hereby disclaimed, including fitness for merchantability and buyer's intended use or purpose. All parts are sold "AS IS" except for the limited warranties granted herein. Buyer assumes all risks as to the selection, suitability and performance of all goods and products selected. This limited warranty does not cover damage or impairment in any part due to misuse, improper installation, accident or contact with on-road or off-road hazards, product modification, improper or inadequate cleaning and/or maintenance. Smittybilt is not responsible for items damaged during shipping. This warranty is not transferable from the original buyer. For the original Buyer to be eligible for the limited warranty coverage, the Buyer must provide proof of purchase. Smittybilt strongly recommends returning the warranty registration card.

Customer's remedy hereunder shall be limited only to repair or replacement (at Smittybilt's option) of any defective part(s) returned to Smittybilt at customer's expense. The determination of whether or not a returned part is defective or subject to coverage under the limited warranties stated herein shall be made at Smittybilt's sole discretion.

To assure product quality, Smittybilt reserves the right to change product design, material, specification and finishes without prior notice to customers. This limited warranty gives you specific legal rights and you may also have other rights, which may vary from state to state. Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply as to you. Also, some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. Smittybilt reserves the right to discontinue product lines and substitute products, or provide other remedies than those listed in this limited warranty for those discontinued products.

### Warning

Rollover and other types of vehicle accidents may result in serious injury or death to you, your passengers and others sharing the road. Smittybilt accessories are decorative and are not intended to reduce or avoid injury or damage in the event of an accident. The weight and location of Smittybilt accessories may affect your vehicles' handling, stability and performance, creating an increased risk of accident or rollover. Before installing any accessory, check state laws and assure that the accessory will not obscure any lights or interfere with proper operation on your vehicle's safety equipment. Consult your owner's manual and the Smittybilt instructions, or additional safety information. Smittybilt products, nor the warnings contained herein, are not a substitute for your safe driving. Don't drink and drive, always use seat belts and don't drive faster than conditions permit.

**For Technical Support/Warranty Information please call 310-762-9944**

**Smittybilt, 400 West Artesia Blvd, Compton, CA 90220**