



WWW.SMITTYBILT.COM


Installation Instructions
XRC FRONT BUMPER BULL BAR
1984-2001 Jeep Cherokee XJ
Part #: S/B76811

NOTE: Carefully read this entire instruction manual thoroughly before attempting to assemble and/or install this product. Photos may differ slightly from your vehicle and the parts you receive; the installation process will remain the same.

Parts Included	QTY
93-8247 XJ XRC BUMPER BULL BAR	1
76811HDW – HARDWARE PACK:	1
M12-1.75X35MM HEX BOLT 10.9	8
M12-1.75 NYLOCK NUT	8
M12 FLAT WASHER	8

Installation:

Step 1: Carefully place your new bull bar attachment (**93-8247**) on top of your XRC Front Bumper (**76810**). Align the bull bar with the holes pre-drilled in the bumper. Install the hardware as shown in (**Figure A**).



For Technical Support/Warranty Information please call 1-800-776-0767
Smittybilt, 400 W. Artesia Blvd Compton, CA 90220



WWW.SMITYBILT.COM

Installation Instructions
XRC FRONT BUMPER BULL BAR
1984-2001 Jeep Cherokee XJ
Part #: S/B76811

Step 2: Torque down the **M12** hardware to **30 ft-lbs.**



Fig. B

Step 3: Installation is now complete. **(Figure B)**

For Technical Support/Warranty Information please call 1-800-776-0767
Smittybilt, 400 W. Artesia Blvd Compton, CA 90220



WWW.SMITTYBILT.COM

Installation Instructions
XRC FRONT BUMPER BULL BAR
1984-2001 Jeep Cherokee XJ
Part #: S/B76811

Use this only as a guide for hardware without a called-out torque specification in the instruction manual

Bolt Torque and ID						
Decimal System			Metric System			
All Torques in Ft. Lbs.						
Bolt Size	Grade 5	Grade 8	Bolt Size	Class 9.8	Class 10.9	Class 12.9
5/16	15	20	M6	5	9	12
3/8	30	45	M8	18	23	27
7/16	45	60	M10	32	45	50
1/2	65	90	M12	55	75	90
9/16	95	130	M14	85	120	145
5/8	135	175	M16	130	165	210
3/4	185	280	M18	170	240	290

1/2-13x1.75 HHCS
 Grade 5 Grade 8
 (No. of Marks + 2)

D T L X

M12-1.25x50 HHCS

D T L X

G = Grade (Bolt Strength)
 D = Nominal Diameter (Inches)
 T = Thread Count (Threads per Inch)
 L = Length (Inches)
 X = Description (Hex Head Cap Screw)

P = Property Class (Bolt Strength)
 D = Nominal Diameter (Millimeters)
 T = Thread Pitch (Thread Width, mm)
 L = Length (Millimeters)
 X = Description (Hex Head Cap Screw)

For Technical Support/Warranty Information please call 1-800-776-0767
 Smittybilt, 400 W. Artesia Blvd Compton, CA 90220



WWW.SMITYBILT.COM

**Installation Instructions
XRC FRONT BUMPER BULL BAR
1984-2001 Jeep Cherokee XJ
Part #: S/B76811**

Limited Warranties

Smittybilt's products are covered under the following limited warranties only. Note that the duration of the limited warranty differs according to the material and finish of the product purchased. Subject to the duration and conditions of the limited warranty stated below, Smittybilt warrants to the original retail purchaser that its products are free from defects in material and workmanship. All other warranties and representations express or implied, are hereby disclaimed, including fitness for merchantability and buyer's intended use or purpose. All parts are sold "AS IS" except for the limited warranties granted herein. Buyer assumes all risks as to the selection, suitability and performance of all goods and products selected. This limited warranty does not cover damage or impairment in any part due to misuse, improper installation, accident or contact with on road or off-road hazards, product modification, improper or inadequate cleaning and/or maintenance. Smittybilt is not responsible for items damaged during shipping. This warranty is not transferable from the original buyer. For the original Buyer to be eligible for the limited warranty coverage, the Buyer must provide proof of purchase. Smittybilt strongly recommends returning the warranty registration card. Customer's remedy hereunder shall be limited only to repair or replacement (at Smittybilt's option) of any defective part(s) returned to Smittybilt at customer's expense. The determination of whether or not a returned part is defective or subject to coverage under the limited warranties stated herein shall be made at Smittybilt's sole discretion. To assure product quality, Smittybilt reserves the right to change product design, material, specification and finishes without prior notice to customers. This limited warranty gives you specific legal rights and you may also have other rights, which may vary from state to state. Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply as to you. Also, some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. Smittybilt reserves the right to discontinue product lines and substitute products or provide other remedies than those listed in this limited warranty for those discontinued products.

Warning

Rollover and other types of vehicle accidents may result in serious injury or death to you, your passengers and others sharing the road. Smittybilt accessories are decorative and are not intended to reduce or avoid injury or damage in the event of an accident. The weight and location of Smittybilt accessories may affect your vehicles' handling, stability and performance, creating an increased risk of accident or rollover. Before installing any accessory, check state laws and assure that the accessory will not obscure any lights or interfere with proper operation on your vehicle's safety equipment. Consult your owner's manual and the Smittybilt instructions, or additional safety information. Smittybilt products, nor the warnings contained herein, are not a substitute for your safe driving. Don't drink and drive, always use seat belts, and don't drive faster than conditions permit.



**WARNING: Cancer and Reproductive Harm -
www.P65Warnings.ca.gov.**

***Jeep, Wrangler, Rubicon,
Renegade, CJ, Quada Trac and
the Jeep Grille Design are
Registered trademarks of FIAT
Chrysler Automotive (FCA)***

**For Technical Support/Warranty Information please call 1-800-776-0767
Smittybilt, 400 W. Artesia Blvd Compton, CA 90220**



WWW.SMITTYBILT.COM

Installation Instructions
XRC FRONT BUMPER BULL BAR
1984-2001 Jeep Cherokee XJ
Part #: S/B76811

Product cleaning and maintenance instructions

Stainless Steel Finish – Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap, window or glass cleaner may be used to clean the finish.

Dual state powder coat finish – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish, you may wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or wax that contains abrasive that could damage the finish.

Textured coated finishes should be cleaned with a mild soap on a damp sponge. Do not apply polish or wax that requires to be removed by means of buffing. This type of wax is commonly used at car wash facilities.

Chrome Finish – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish, you should wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or wax that contains abrasive that could damage the finish.

Always periodically check that all hardware is tight. This should be done 200 miles after installation and periodically after.

For Technical Support/Warranty Information please call 1-800-776-0767
Smittybilt, 400 W. Artesia Blvd Compton, CA 90220